

	<b>FINAL TERM EXAMINATION</b> SPRING 2006 CS201 - INTRODUCTION TO PROGRAMMING (Session - 1 )	Marks: 50 Time: 120min
--	---	---------------------------

StudentID/LoginID: \_\_\_\_\_

Student Name: \_\_\_\_\_

Center Name/Code: \_\_\_\_\_

Exam Date:                      Wednesday, August 23, 2006

**Please read the following instructions carefully before attempting any of the questions:**

1. Attempt all questions. Marks are written adjacent to each question.
2. Do not ask any questions about the contents of this examination from anyone.
  - a. If you think that there is something wrong with any of the questions, attempt it to the best of your understanding.
  - b. If you believe that some essential piece of information is missing, make an appropriate assumption and use it to solve the problem.
  - c. Write all steps, missing steps may lead to deduction of marks.
  - d. All coding questions should be answered using the **C++** syntax.

You are allowed to use the Dev-C++ compiler to write and test your code. If you do so please remember to copy and paste your code into the examination solution area. **(Do NOT share your code; your colleague could get higher marks than you!!)**

**\*\*WARNING: Please note that Virtual University takes serious note of unfair means. Anyone found involved in cheating will get an `F` grade in this course.**

For Teacher's use only											
Question	1	2	3	4	5	6	7	8	9		Total

Marks												
-------	--	--	--	--	--	--	--	--	--	--	--	--

Question No: 1 ( Marks: 2 ) - Please choose one

A **for** loop usually consist of \_\_\_\_\_ expressions.

▶ 1

▶ 3

▶ 2

▶ 4

Question No: 2 ( Marks: 2 ) - Please choose one

A preprocessor directive is identified by \_\_\_\_\_ symbol

▶ #

▶ {

▶ (

▶ ~

Question No: 3 ( Marks: 2 ) - Please choose one

Which of the following operators can not be overloaded?

▶ new

▶ delete

▶ +=

▶ sizeof

Question No: 4 ( Marks: 2 ) - Please choose one

Analyze the following code

```
class myclass
{
private:
float x,y;
public:
void myclass(float a, float b)
{
x=a;
y=b;
}
void diplay()
{
cout<<endl<<x<<endl<<y;
}
};
```

What is wrong with the above code?

- ▶ The member functions should be private
- ▶ constructor must not have a return type
- ▶ The constructor should have no body
- ▶ There is no error in the given code

Question No: 5 ( Marks: 6 )

Analyze the following code and list all the errors and line numbers in the given code.

```
int i=2;
for(i<=100;i++)
{
if(i%2==0)
{
cout<<i;
cout<<" is even /n';
}
}
```

Question No: 6 ( Marks: 7 )

Declare a class **student** having the following data members and member functions in the

class.  
**stdno(integer)**  
**stdname(character array of size 20)**  
**phone(long integer)**

**getdata()** function that will read data into members data.  
**Display()** function that will display the data on the screen.

Question No: 7 ( Marks: 6 )

- a. Write the statement that will create an array of 10 objects of the class **student** and place the base address of the array in a pointer **ptr** of the class **student** given in Question No. 6.
- b. Write the code of the parameterized constructor for the class **student** given in Question No. 6.

Question No: 8 ( Marks: 15 )

Write a program that will create a class **distance**. The class **distance** consist of two data members **feet** and **inches**, both of types float. The class distance consist of two member functions, **getdata()** and **show()**. The function **getdata()** is used to read data from the user through keyboard into **feet** and **inches**. The **show()** function is used to display the values of **feet** and **inches** on the screen.

The program will create two objects **dest1** and **dest2** of the class **distance**. The program will read data into **dest1** and **dest2** using **getdata()**. The program will create another object **dest3** of the class **distance** by overloading the minus “-“operator trough expression **dest3=dest1-dest2**. The program will then display **dist3** on the screen using **show()** function. The program also takes care of the fact that distance can not be negative. If **dest2** is larger then **dest1** then **dest3** should not be created and program should display the message “**Distance can not be negative**”.

Question No: 9 ( Marks: 8 )

What are the benefits of the templates?